

# \* ギア性能一覧表 \*

ギア名称	減速比	ギア 段数	L寸法	許容トルク		瞬時最大負荷		許容ラジアル荷重		許容スラスト荷重					
			mm	mN-m	kg-cm	mN-m	kg-cm	N	kgf	N	kgf				
TU	15 20 26	2	25.4	49	0.5	73.5	0.75	4.9	0.5	4.9	0.5				
	59 78 101 133	3		98	1	147	1.5								
	231 303 396 517 677	4	30	196	2	294	3								
UW	4 6	1	19.1	49	0.5	73.5	0.75	9.8	1	19.6	2				
	16 24 36	2	26.4	98	1	147	1.5								
	64 96 144 216	3	33.7	147	1.5	220.5	2.25								
	256 384 576 864 1296	4	41	196	2	294	3								
UM	4 6	1	29.1	490	5	735	7.5	29.4	3	39.2	4				
	16 24 33	2	39.1	980	10	1470	15								
	67 94 133 188	3	49.1	1470	15	2205	22.5								
	272 383 540 763 1076	4	59.1	1960	20	2940	30								
KH ・ PH	5 10	2	18.7	98	1	147	1.5	9.8	1	6.86	0.7				
	15 20 25 30	3	21.2	196	2	294	3								
	40 50 60 75	4	23.7	294	3	441	4.5								
	100														
	120 150 200 270 300	5	26.2	588	6	882	9								
450 675 900	6	28.7													
KJ ・ PJ	5 10	2	20.3	98	1	147	1.5	9.8	1	6.86	0.7				
	15 20 25 30	3	22.8	196	2	294	3								
	40 50 60 75	4	25.3	294	3	441	4.5								
	100														
	120 150 200 270 300	5	27.8	588	6	882	9								
450 675 900	6	30.3													
KS ・ PS	10	2	20.2	98	1	147	1.5	9.8	1	6.86	0.7				
	33	3	23.7	196	2	294	3								
	66 75	4	27.2	294	3	441	4.5								
	100														
	150 200 225 300	5	30.7	588	6	882	9								
450 600 675 900	6	34.2													
KZ	5 10	2	18.7	98	1	147	1.5	9.8	1	6.86	0.7				
	15 20 25 30	3	21.2	196	2	294	3								
	40 50 60 75 100	4	23.7												
	120 150 200 270 300	5	26.2	294	3	441	4.5								
	450 675 900	6	28.7												
KW ・ KWR	25 30 50	2	-	196	2	294	3	9.8	1	6.86	0.7				
	60 75 100	3		294	3	441	4.5								
	125 150	4		588	6	882	9								
	200 250 300 375 500														
	750 1000 1500														
HA	15 30	2	11	49	0.5	73.5	0.75	2.94	0.3	4.9	0.5				
	60	3													
	80 120 160 200 240 300 400 500	4										68.6	0.7	102.9	1.05
	1000 1500 2000 2500 3000 3750	5										98	1	147	1.5
IA IAL	70 90 190	5	19	392	4	588	6	9.8	1	9.8	1				
	220 250 290 450			588	6	882	9								
IB IBL	70 90 190	5	19	392	4	588	6	19.6	2	9.8	1				
	220 250 290 450			588	6	882	9								
IG IGL	60 100 130	4	19	392	4	588	6	9.8	1	9.8	1				
	230 280 320 500	5		588	6	882	9								
IM IML	60 100 130	4	19	392	4	588	6	19.6	2	9.8	1				
	230 280 320 500	5		588	6	882	9								
CE	5 10	2	27	294	3	441	4.5	29.4	3	19.6	2				
	15			490	5	735	7.5								
	18 25 30 36	3		686	7	1029	10.5								
	50 60														
	75 100 120 150 200			4	980	10	1470					15			
250 300 500 750 1000	5														
CM	5 10 12.5	2	30	980	10	1470	15	39.2	4	29.4	3				
	15 18 25 30 36	3	35	1568	16	2352	24								
	50 60 75 100 120 150 180	4	42	2450	25	3675	37.5								

# \* ギア性能一覧表 \*

ギア名称	減速比	ギア 段数	L寸法 mm	許容トルク		瞬時最大負荷		許容ラジアル荷重		許容スラスト荷重	
				mN-m	kg·cm	mN-m	kg·cm	N	kgf	N	kgf
SW	48 65	4	-	3920	40	5880	60	392	40	117.6	12
	125			7840	80	11760	120				
	125 150 210			9800	100	14700	150				
	300 525			750	1050	5					
	750 1050	5									
LG ・ LGL	6 10 15 20	3	25	1960	20	2940	30	98	10	19.6	2
	25 30 36			2940	30	4410	45				
	50			3430	35	5145	52.5				
	75 100 150 200	4		3920	40	5880	60	137	14		
	300			4900	50	7350	75				
	500 750 1000	5		7840	80	11760	120				
FG FGL	30 50	3	26	980	10	1470	15	29.4	3	19.6	2
	500 700 1000	4		1960	20	2450	25				

ギアドモーター

TU	1627
HA	2732
KH・PH	2937
KJ・PJ	3522N
KS・PS	2932
KZ	3526N
KW・KWR	3526
IA・IB	3038
IG・IM	3442
CE	3452
CM	3850
LG	4668
FG	2234
	3641

スリーピース株式会社 営業部  
 TEL:03-5807-3051 FAX:03-3831-7727  
 URL :<http://www.three-peace.com>  
 E-mail:[eigyou@three-peace.com](mailto:eigyou@three-peace.com)

- 本カタログに掲載されております製品ならびに製品仕様は、予告なしに変更する場合があります。
- 本カタログに記載されておりますコンテンツを、弊社の承諾なしに転載および複製することは、固くお断りいたします。
- 弊社製品のコピー品ならびに類似品にはご注意ください。